APAC Infrastructure Pty Ltd
ABN: 43 615 637 235
1300 952 788
sales@apacinfrastructure.com.au

AL220 Torque Arm - Anti-Twist for Guyed Towers

AP-AL220-TA



Key Features

- Up to six-way guying
- Bolt-together aluminium design
- Increases torsional resistance on AL220 guyed towers
- Part of the AL220 Ecosystem

Overview

Anti-twist torque arm assemblies are used to provide up to six-way guying to increase torsional resistance on towers supporting microwave/pencil beam antennas or surveillance cameras.

Attached to standard APAC AL220 aluminium lattice towers at any section by three heavy duty U-bolt clamps (not pictured). This system has been designed specifically to match APAC AL220 ground and roof mounted aluminium lattice towers (220 mm faced, 40 x 3 mm round tube).

This is a subcomponent of the AL220 Anti-Twist Torque Arm Kits which are supplied to match your tower height, however this can be supplied as a stand-alone part if requested.

APAC Infrastructure Pty Ltd
ABN: 43 615 637 235
1300 952 788
sales@apacinfrastructure.com.au

Specification

Parameter	AP-AL220-TA
Physical Specification	
System	**AL220**
Subtype	**Attachment**
Materials	**Aluminium**
Mounting	**AL220 Triangular Uprights**
Interfaces	
Installation / Attachment	

Quantity	Mounting	Notes
1	AL220 Triangular Uprights	3x U-Bolts clamp around AL220 upright

Subcomponents

Quantity	Item	Materials	Material Finish
1	Bolt together assembly	Aluminium 6005-T5	Bright/Pickled Finish

Quantity	Bundled Components
3	U-Bolt, 40 mm Rounded, 100 mm Long (AP-FST-UB40-100)

Australian designed and manufactured infrastructure for public safety and first response, built on the Sunshine Coast, Queensland. Need a variation on this design? Our team can engineer it to suit your site.

Contact us

Phone 1300 952 788
Email sales@apacinfrastructure.com.au
Web apacinfrastructure.com.au
ABN 43 615 637 235

Specifications, dimensions and weights are nominal, correct at the date of issue and subject to change without notice. Images are for illustration and may show optional equipment. Confirm suitability for your site, including wind region and mounting surface, with APAC before ordering, and install in accordance with APAC's instructions and the relevant Australian Standards.

Issued 11 November 2026. For the latest version of this datasheet, visit https://apacinfrastructure.com.au/product-catalogue/supports-stabilisers/al220-torque-arm-anti-twist-guyed-towers?v=507

© 2026 APAC Infrastructure Pty Ltd. All rights reserved.