APAC Infrastructure Pty Ltd
ABN: 43 615 637 235
1300 952 788
sales@apacinfrastructure.com.au

GG48 Galvanised Steel Guyed Climbable Roof Mast, 4m

AP-GG48-4



Key Features

- Heights from 4 to 6 metres
- Serviceable mast, one person install
- Rotatable mast 360deg without the need to lower
- Galvanised 48 mm (OD) steel pole
- Compatible with the GC48 accessory ecosystem

Overview

Site engineers are often faced with the challenge of achieving sufficient height while maintaining project cost. APAC's GG48 guyed steel roof masts meets the challenge for a medium height with exceptional affordability. It can be rotated the full 360 degrees while erected, allowing the tech to perform azimuthal adjustments safely.

The split section design reduces shipping length under three metres, allowing transport anywhere in the globe. This clever design also allows the addition of any GC48 accessory such as a cluster or sector mounting frame.

GG48 has a climbable variation ~~GP48~~ that has welded foot pegs.

Designed and built by APAC in the Sunshine Coast, Australia, you can expect uncompromising standards and a robust, real-world tested mast that will provide the peace of mind that it will perform it's intended role for many years to come.

APAC Infrastructure Pty Ltd
ABN: 43 615 637 235
1300 952 788
sales@apacinfrastructure.com.au

Specification

Parameter	AP-GG48-4
Physical Specifications	
System	**GC48**
Subtype	**Mounts**
Height (Nominal)	**4 m**
Materials	**Steel**
Material Finish	**Hot-Dip Galvanised**
Weight	**9 kg**
Installation	**Roof Mounted**
Mounting	**Screw / Bolt**
Interfaces	

Installation / Attachment

Quantity	Mounting	Notes
4	Screw / Bolt	Attach Hinging Base to Existing Roof Structure
6	Screw / Bolt	Attach Guy Anchor Plates to Roof

Payload Interfaces

Quantity	Interfaces	Notes
1	Pole 48 mm ⌀	For attaching ordinary equipment
1	Pole Spigot, 48 mm ⌀ OD	For slotting headframes over the top

Subcomponents

Quantity	Item	Materials	Material Finish
1	3m Steel CHS Pipe	Steel	Galvanised Coating
1	1m Steel CHS Extension	Steel	Galvanised Coating

Quantity	Bundled Components
1	GC48 Centre Foot Base Plate (AP-GC48-CBP)
3	Guy Wire Cleat - Single Anchor, Galvanised (AP-FST-GWCSA)
1	AL220 Guy Wire Kit - Galvanised, Suit 3.4m Tower (AP-AL220-GWK-GAL-3.4)

Variants

GG48 Galvanised Steel Guyed Climbable Roof Mast, 4m AP-GG48-4 · this datasheet	
GG48 Galvanised Steel Guyed Climbable Roof Mast, 5m AP-GG48-5	
GG48 Galvanised Steel Guyed Climbable Roof Mast, 6m AP-GG48-6	

Australian designed and manufactured infrastructure for public safety and first response, built on the Sunshine Coast, Queensland. Need a variation on this design? Our team can engineer it to suit your site.

Contact us

Phone	1300 952 788
Email	sales@apacinfrastructure.com.au
Web	apacinfrastructure.com.au
ABN	43 615 637 235

Specifications, dimensions and weights are nominal, correct at the date of issue and subject to change without notice. Images are for illustration and may show optional equipment. Confirm suitability for your site, including wind region and mounting surface, with APAC before ordering, and install in accordance with APAC's instructions and the relevant Australian Standards.

Issued 11 November 2026. For the latest version of this datasheet, visit https://apacinfrastructure.com.au/product-catalogue/mounting-structures/gg48-galvanised-steel-guyed-climbable-roof-mast-6m?v=584

© 2026 APAC Infrastructure Pty Ltd. All rights reserved.