APAC Infrastructure Pty Ltd
ABN: 43 615 637 235
1300 952 788
sales@apacinfrastructure.com.au

Pad-Mount Enclosure Interface Bracket for Wescor AL5 to suit DTP3 Platforms

AP-DTP3-PMEIF-AL5



Key Features

- Mounts a Wescor AL5 cabinet or AL5 power system on a DTP3 platform
- Two aluminium RHS bearers on the DTP3 grid
- Lifts the cabinet clear of the floor and side channel
- Stainless steel fixings

Overview

This interface bracket mounts a Wescor AL5 battery and equipment cabinet, or an APAC AL5 solar power system, at one end of a DTP3 platform such as the AP-DTP3SK skid or the AP-DTP3JF jackframe. Two 75 x 50 x 3 mm aluminium RHS bearers lie along the platform on two of the DTP3 grid's hole lines, across its end and inner mounting runners and on over the forklift pocket. Eight M12 bolts hold them down through the runners' grid holes, with crush tubes inside the bearers.

The cabinet's base flanges bolt to the bearers at its anchor holes: through to the end runner on the outside, and into tapped nut bars inside the bearers on the inside. The bearers lift the cabinet 25 mm over the side channel and the floor, so it can stand at the platform's front edge without overhanging it. All fixings are stainless steel.

APAC Infrastructure Pty Ltd
ABN: 43 615 637 235
1300 952 788
sales@apacinfrastructure.com.au

Specification

Parameter	AP-DTP3-PMEIF-AL5
Physical Specification	
System	**DTP3**
Subtype	**Interface Bracket**
Materials	**Aluminium**
Material Finish	**Bright/Pickled Finish**
Mounting	**Screw / Bolt**
Dimensions	**1,524 × 575 × 90 mm**
Weight	**6 kg**
Interfaces	

Installation / Attachment

Quantity	Mounting	Notes
8	Screw / Bolt	Two bearers on two DTP3 grid lines 500 mm apart, over the end and inner runners: two M12 bolts at each runner's grid holes

Available Interfaces

Quantity	Interfaces	Notes
4	Screw / Bolt	The Wescor AL5's four base flange anchor holes

Subcomponents

Quantity	Item	Materials	Material Finish
2	75x50x3 mm RHS Bearer	Aluminium	Bright/Pickled Finish
10	Crush Tube	Aluminium	Bright/Pickled Finish
2	Tapped Nut Bar	Aluminium	Bright/Pickled Finish

Quantity	Bundled Components
8	Hex Bolt, Stainless Steel - M12 x 80mm Standard Thread (AP-FSS-HXB-M12-80)
2	Hex Bolt, Stainless Steel - M12 x 50mm Standard Thread (AP-FSS-HXB-M12-50)
8	Hex Nut, Stainless Steel - M12 Standard Thread (AP-FSS-HXN-M12)
18	Flat Washer, Stainless Steel - M12 (AP-FSS-FW-M12)

Australian designed and manufactured infrastructure for public safety and first response, built on the Sunshine Coast, Queensland. Need a variation on this design? Our team can engineer it to suit your site.

Contact us

Phone	1300 952 788
Email	sales@apacinfrastructure.com.au
Web	apacinfrastructure.com.au
ABN	43 615 637 235

Specifications, dimensions and weights are nominal, correct at the date of issue and subject to change without notice. Images are for illustration and may show optional equipment. Confirm suitability for your site, including wind region and mounting surface, with APAC before ordering, and install in accordance with APAC's instructions and the relevant Australian Standards.

Issued 29 November 2026. For the latest version of this datasheet, visit https://apacinfrastructure.com.au/product-catalogue/base-plates-interfaces/pad-mount-enclosure-interface-bracket-wescor-al5-suit-dtp3?v=854

© 2026 APAC Infrastructure Pty Ltd. All rights reserved.